

Real Single Particle Passing Thru Finite Surface ΔS

Fig.1






Fig.2




Subset of Rays Traversing 2D Grid System from Reference Surface ${\it Fig.3}$




Rays within a particular Ray Set $\Delta\Re$ from a Reference ΔS Occupying Solid Angle Group $\Delta\Omega$ Traversing Voxels

Fig.4



An LVG From A Reference Voxel Surface 2D or Overhead View

Fig.5



Pointer/Transport Multiplier Memory Device

Fig.6





Fig. 7



Pre-Computed Ray Set Geometric Properties (Figure 7, Block 2AI Embodiment)

Fig.8

```
7/15
1 12927 [0][0][0] - 10
2 [0][0][0]-336-:336-|0,4:1,2:37,2:73,2:109,4:110,2:146,2:182,1:188,4:189,2:
3 336
4 336
57.850558564946638e-056.784620633418995e+006.623391839641562e+002.81960000000000e-06
6 - [0][0][0] - 4 - 1.019279586938127e+00
7 - [0][0][1] - 2 - 9.413711183984186e-02
8 - [1][0][1] - 2 - 1.113416698777977e+00
9 - [2][0][1] - 2 - 1.113416698777977e+00
10 - [3][0][1] - 4 - 8.578329108772469e-02
11 - [3][0][2] - 2 - 1.027633407690246e+00
12 - [4][0][2] - 2 - 1.113416698777977e+00
13 - [5][0][2] - 1 - 1.205002778411613e-01
14 - [5][1][2] - 4 - 1.452034161741309e-01
15 - [5][1][3] - 2 - 8.477130047626756e-01
16 3 detail
17 0 6.659682137068683e+00 6.677133394014817e+00 6.623885099075124e+00
   5.176445578231292e-01 - 6.677134770900707e+00
19
       9.869710645786067e-01
20
       1.229759582661787e-01
21
       1.109947022844781e+00
22
       1.109947022844781e+00
23
       9.590364158782305e-02
24
       1.014043381256952e+00
25
       1.109947022844781e+00
26
       1.418524854996891e-01
27
       1.729307559421361e-01
28
       7.951637814029552e-01
29 1 6.697852583372446e+00 6.730875835863125e+00 6.677135463944154e+00
   4.295457766439909e-01 - 6.730877702159851e+00
31
       1.049588508542006e+00
32
      6.672025535341053e-02
33
       1.116308763895405e+00
34
       1.116308763895405e+00
35
       8.023541120737232e-02
36
       1.036073352688041e+00
37
       1.116308763895405e+00
38
       1.034249093947345e-01
39
       1.237661683734199e-01
40
       8.891176861272597e-01
41 2 6.743640693621075e+00 6.780941997558494e+00 6.730879046744218e+00
42 5.280966553287982e-02 - 6.784620633418995e+00
43
       1.094353538739710e+00
44
       2.958657686380297e-02
45
       1.123940115603512e+00
46
       1.123940115603512e+00
47
       3.584565699482696e-02
48
       1.088094458608688e+00
                                    Sample Prototype Code Output Fragment from
49
       1.123940115603512e+00
                                         Figure 8 Pre-Computational Process
50
       4.868157770248906e-02
51
       5.259631315096771e-02
                                      Fig.9
52
       1.022662224750057e+00
```







Fig. 10



Inline Ray Set Based LVG Discrete Particle Transport Multipliers (Figure 7, Block 2 Embodiment)



Sample Interaction Model for Radiation (Figure 7, Block 5 Non-Fissile Embodiment)



2.02%

1.15%

1.84%

0.96%

0.83%

0.94%

2.9424E-04

2.9711E-04

3.1986E-04 3.1720E-04

3.8524E-04 3.8161E-04

Plane 4 Total Sum 0.21% 7.2366E-03 7.2516E-03

0.8%

0.00%

0.76%

-1.99%

-0.58%

-0.69%

4.9014E-05

4.8680E-05

3.4150E-05

3.4570E-05

5.8650E-05 5.7375E-05

6.4404E-05 6.2589E-05

4.2318E-05 4.2186E-05

2.3141E-05 2.2726E-05

1.4523E-05 1.4176E-05 0.31%

1.80%

2.39%

2.95%

2.10%

1.69%

0.08%

1.69%

0.33%

2.8368E-05 2.8356E-05

0.0000E+00 0.0000E+00

7.7734E-05 7.7144E-05

5.9359E-05 6.0540E-05

4.8330E-05 4.8612E-05

3.1472E-05

3.2430E-05

8.2537E-05 8.0804E-05

1.4031E-04 1.379年-04

1.3593E-04

1.3441E-04 1.3213E-04

1.5681E-04 1.5629E-04

1.3582E-04

2.2% 0.92%

Present Invention

% Difference

Monte Carlo

₹

8.4336E-05 8.3562E-05 7.4409E-05 7.2760E-05 5.2384E-05 5.1326E-05 1.2% 0.16% 2.3132E-04 2.018年-04 1.9937E-04 1.3739E-04 1.3899E-04 1.67% 2.6043E-04 2.5564E-04

0.05%

0.38%

0.29%

2.3168E-04 0.47% 4.5825E-04 3.9478E-04 3.8819E-04 4.6043E-04

> -1.2% 5.9632E-04

> > -0.83%

-1.23%

8.4715E-04

8.3684E-04

5.8915E-04

6.8796E-04 6.9370E-04 4.9065E-04 4.9042E-04

5.6220E-04

6.8319E-04 6.8121E-04

5.6004E-04

Planer Interaction Rate Results Plane 4

| (cm) x, y, z 5, 5, 5 | (GMVP) Base Case | 200 | | | | | | | | |
|----------------------------|------------------|--------------|---------------------------------|----------|--------------|----------|---------------------|----------|---------------------------------|----------|
| (cm) x, y, 5, 5, | | Case | | | | | | | | |
| , ×, ×, | Point Flux | FSD | Node Avg. Flux | Absolute | Point Flux | Absolute | Point Flux | Absolute | Point Flux. | Absolute |
| က် | z cm² s¹ | (%) 0 | cm ² s ⁻¹ | % Error | cm² s¹ | % Error | cm² s ⁻¹ | % Error | cm ² s ⁻¹ | % Error |
| | 5 5.9566E+00 | 0.000 | 6.0400E+00 | 1.40% | 5.9216E+00 | 0.59% | 5.7700E+00 | 3.13% | 5.9670E+00 | 0.17% |
| 15, 5, | 5 1.3719E+00 | 0.000 | 1.3560E+00 | 1.16% | 1.3062E + 00 | 4.79% | 1.6300E+00 | 18.82% | • | • |
| 25, 5, | 5 5.0087E-01 | 0.000 | 5.0290E-01 | 0.41% | 4.8947E-01 | 2.28% | 4.4600E-01 | 10.96% | • | 1 |
| 1Ai 35, 5, | 5 2.5243E-01 | 0.000 | 2.5460E-01 | 0.86% | 2.4824E-01 | 1.66% | 2.9200E-01 | 15.68% | • | • |
| 45, 5, | 5 1.5026E-01 | 0.000 | 1.5060E-01 | 0.23% | 1.4818E-01 | 1.38% | 1.6000E-01 | 6.48% | • | • |
| 55, 5, | 5 5.9529E-02 | 0.000 | 5.8166E-02 | 2.29% | 5.8810E-02 | 1.21% | 6.6900E-02 | 12.38% | 7.0861E-02 | 19.04% |
| 65, 5, | 5 1.5328E-02 | 0.000 | 1.5283E-02 | 0.30% | 1.5165E-02 | 1.07% | 1.7100E-02 | 11.56% | 1.8687E-02 | 21.91% |
| 75, 5, | 5 4.1769E-03 | 0.000 | 4.2170E-03 | %96.0 | 4.1358E-03 | 0.98% | 3.3300E-03 | 20.28% | 5.0464E-03 | 20.82% |
| 85, 5, | 5 1.1853E-03 | 0.000 | 1.2186E-03 | 2.81% | 1.1743E-03 | 0.93% | 7.4400E-04 | 37.23% | 1.3882E-03 | 17.11% |
| 95, 5, | 5 3.4685E-04 | 0.000 | 3.2850E-04 | 5.29% | 3.4377E-04 | 0.89% | 3.2200E-04 | 7.16% | 3.8732E-04 | 11.67% |
| 5, 5, 5 | 5 8.2926E+00 | 0.021 | 8.290E + 00 | 0.03% | 8.2597E+00 | 0.40% | 7.9400E+00 | 4.25% | 8.2595E+00 | 0.40% |
| 15, 5, 5 | 5 1.8703E+00 | 0.005 | 1.827E+00 | 2.31% | 1.8345E+00 | 1.91% | 2.1800E+00 | 16.56% | • | • |
| 25, 5, | 5 7.1398E-01 | 0.003 | 7.051E-01 | 1.24% | 7.1045E-01 | 0.49% | 6.4500E-01 | 899.6 | 1 | • |
| 1Ali 35, 5, | 5 3.8469E-01 | 0.004 | 3.692E-01 | 4.03% | 3.6632E-01 | 4.77% | 4.3000E-01 | 11.78% | | • |
| 45, 5, | 5 2.5398E-01 | 9000 | 2.485E-01 | 2.16% | 2.3171E-01 | 8.77% | 2.6200E-01 | 3.16% | • | • |
| 55, 5, | 5 1.3722E-01 | 0.073 | 1.304E-01 | 4.97% | 1.3236E-01 | 3.54% | 1.4600E-01 | 6.40% | 1.5426E-01 | 12.42% |
| 65, 5, | 5 4.6591E-02 | 0.117 | 4.611E-02 | 1.03% | 4.7617E-02 | 2.20% | 4.8400E-02 | 3.88% | 5.3594E-02 | 15.03% |
| 75, 5, | 5 1.5877E-02 | 0.197 | 1.604E-02 | 1.03% | 1.6049E-02 | 1.09% | 1.5400E-02 | 3.00% | 1.8164E-02 | 14.41% |
| 85, 5, | 5 5.4704E-03 | 0.343 | 5.496E-03 | 0.47% | 5.2495E-03 | 4.04% | 5.0800E-03 | 7.14% | 6.1428E-03 | 12.29% |
| 95, 5, | 5 1.8508E-03 | 0.619 | 1.903E-03 | 2.80% | 1.6929E-03 | 8.53% | 1.2400E-03 | 33.00% | 2.0208E-03 | 9.19% |

Kobayashi International 3D Benchmark Problem 1A Comparison

| 88 | Distance | Morte Carlo | 0 | Present Invention | E P | Present Invention | ention | Present Invention | ention |
|-----------|----------|--------------------|--------------|-------------------|----------|-------------------|----------|-------------------------|----------|
| | | (GIVINT) BASE CASE | 333 | | 3 | | T T | | Gell. |
| | (cm) | Paint Rux | 82 | Node Avg. Rux | Absolute | Point Rux | Absolute | Point Flux | Absolute |
| | x,y,z | am² s¹ | (%) 0 | cm² s¹ | %Enar | am² s¹ | %Error | am² s¹ | % Error |
| | 5,5,5 | 5.9566E+00 | 0000 | 6.0645E+00 | 1.81% | | | | |
| | 15,5,5 | 1.3719E+00 | 0.000 | 1.3911E+00 | 1.40% | | | | |
| | 25, 5, 5 | 5.0087E-01 | 0.000 | 5.0110E-01 | 0.05% | | | | |
| ¥ | 35, 5, 5 | 25243E-01 | 0.000 | 25332E-01 | 3.53% | | | | |
| | 45, 5, 5 | 1.5026E-01 | 0.000 | 1.4900E-01 | 0.84% | | | | |
| | 56, 5, 5 | 5.9529E-02 | 0.000 | 5.8632E-02 | 1.51% | 5.9734E-02 | 0.34% | 6.5482E-02 | 10.00% |
| | 65, 5, 5 | 1.5328E-02 | 0000 | 1.5302E-02 | 0.17% | 1.4735E-02 | 3.87% | 1.55421E-02 | 1.40% |
| | 75, 5, 5 | 4.1769E-03 | 0.000 | 4.2007E-03 | 0.57% | 4.0044E-03 | 4.13% | 4.10 66E- 03 | 1.68% |
| | 85, 5, 5 | 1.1853E-03 | 0.000 | 1.2104E-03 | 212% | 1.0669E-03 | 8666 | 1.0993E-03 | 7.26% |
| | 95, 5, 5 | 3.4685E-04 | 0.000 | 3.300ZE-04 | 4.85% | 3.4674E-04 | 0.03% | 3.4294E-04 | 1.13% |

Problem 1Ai No Scatter Surface Cut at x=50 cm Fig. 16

| Problem/Method | Machine | Process Time (sec) |
|-----------------------------|-----------------------------|---------------------|
| Present Invention 1Ai | Pentium Xeon 2.2 GHz 32 bit | 236 Setup 0.01 Exec |
| Present Invention 1Ai Cut | Pentium Xeon 2.2 GHz 32 bit | 163 / 0.021 |
| Present Invention 1Ai Coeff | Pentium Xeon 2.2 GHz 32 bit | 120/ 1.798 |
| Present Invention 1Aii | Pentium Xeon 2.2 GHz 32 bit | 4996 / 33.34 |
| TORT FNSUNCL3 1Ai | FUJITSU AP3000/24 - 296 MHz | 9944 |
| TORT FNSUNCL3 1Aii | FUJITSU AP3000/24 - 296 MHz | 12781 |
| GMVP Base 1Ai | FUJITSU VPP500 100MHz | 1440 |
| GMVP Base 1Aii | FUJITSU VPP500 100MHz | 378,000 |
| ARDRA 1Ai | IBM ASCI Blue-Pacific | 7847 |
| ARDRA 1Àii | IBM ASCI Blue-Pacific | 10223 |
| EVENT 1Ai | AXP1000 667 MHz Alpha | 6344 |
| EVENT 1Aii | AXP1000 667 MHz Alpha | 8357 |

Time Comparison of Present Invention Problem 1Ai and 1Aii